

SPECIFICATIONS

1.1 General Functions

- **Drive Bay:** Vibration damped, holds one front accessible 3.5" FDD, one 5.25" CD-ROM drive, and one internal 3.5" HDD
- **Real Panel:** 6 Slots for PCI/ISA Full-size CPU Card
- **Cooling Fan:** One 12cm / 49 CFM cooling fan with air filter
- **Controls:** Front panel reset & power switch
- **Indicators:** LEDs for system power On/Off and HDD activity
- **Mount Bracket:** Two brackets for vertical and horizontal wall mounting
- **Dimensions:** 260mm (W) x 177mm (H) x 406mm (D)
- **Weight:** Gross 9.5Kg (20.9 lbs); Net 8.5Kg (18.7 lbs)
- **Paint Color:** PANTONE 414U
- **Power Supply:** Field replaceable power supply bracket for both regular PS/2 PSU or PS/2 type redundant PSU

1.2 Mechanical and Environmental

- **Operating Temperature:** 32 to 122 °F (0 to 50 °C)
- **Relative Humidity:** 10 ~ 95% @ 40 °C, non-condensing
- **Vibration (Operation):** 5 ~ 17Hz, 0.1" double-amplitude displacement; 17 ~ 500Hz, 1.5G acceleration peak to peak
- **Shock (Operation):** 10G acceleration peak (11 ms duration)
- **Safety:** TUV approved
- **EMI:** FCC, CE approved

Mechanical Drawing

2.1 Front Panel and Rear Panel



